



NEZONE
HIGH MAST

standing
tall and strong

NEZONE HIGH MAST SPECIFICATIONS

Item	Height	Thickness	Faces	Across face Dia		Base Plate	PCD	Bolt	
				Top	Bottom			Size	Nos
				mm	mm				
NZHM 11	11000	3	12	100	360	545 x 20	445	20 x 900	4
NZHM 12	12000	3	12	100	360	545 x 20	445	20 x 900	6
NZHM 12.5	12500	3,3	12	136	360	560 x 20	460	20 x 900	8
NZHM 16 L	16000	3,3	20	150	360	560 x 25	460	24 x 900	12
NZHM 16 M	16000	3,4	20	150	410	610 x 30	510	30 x 900	12
NZHM 20 L	20000	3,4	20	150	360	560 x 30	460	30 x 900	12
NZHM 20 M	20000	3,4	20	150	460	690 x 32	590	30 x 900	16
NZHM 25	25000	3,4,4	20	150	460	690 x 32	590	30 x 900	16
NZHM 30	30000	3,4,5	20	150	460	690 x 32	590	32 x 900	16

1. Material Of Construction: BSEN 10025/BIS 5836
2. Foundation Bolt Material: Gr Fe-415 Mpa min
3. Base Plate Material: BIS 2062
4. Lantern Carriage Capacity: 750 Kg
5. Protection: Hot Dip Galvanized
6. Galvanization Thickness: 86 Microns (Approx)
7. Type Of Joint: Stress Slip Fit

APPLICATIONS:

1. Airports & Sea Ports
2. Railway Yards
3. Industrial Flood Lighting
4. Car Parks and Junctions
5. Sports Arenas/Stadiums

Corporate Office:

5th Floor, DD Tower, Christian Basti
GS Road, Guwahati 781005, Assam
Phone: +91 361 234 3951/52
email: salesghy@nezonesteel.com
www.nezonesteel.com

Kolkata Office:

Nezone House
19, Jatin Das Road
Kolkata - 700029
Phone +91 - 333 511 5011
Email - nezone@nezonesteel.com

